



5000

Specifications

Tank: Stainless steel with top opening for Servicing

Grate: Base grate is stainless steel,316

Booth: Stainless steel 304, with #4 finish, enclosed on three sides.

Shower Head:10" stainless steel head (8127E)

Activation: Rigid stainless steel pull rod operates a stay open S316 1" ball valve.

EYEWASH

Receptor: 11" stainless steel with #7 bright finish on exterior.

Heads: Stainless steel eyewash heads (SP 18) with integral top dust cover that protect the Heads.

Activation: Rigid stainless steel push flag operate a stay open type S316 ball valve

Sign: Universal emergency sign included.

Bacteriostic Waster Preservative Additive:

This is used to preserve the clean portable water for up to six months

DETAILS

Supply: 1-1/2" Valve

Waste: Open

Optional: Audio Alarm



Disclaimer:

Illustrations, detail drawings and accompanying descriptions describe standard features and sometimes optional variations of each product. They do not necessarily show or describe all the variations available. All designs are subject to change without notice and unless stated in the order, material will be furnished of design in effect at the time the order is filled. As may be necessary, we reserve the right to substitute materials and/or to make changes in design or other specification, as shown and described in any of our printed literature, without liability to purchasers.

Notice: Model shown meet ANSI standard and OSHA rules and regulations relating to this type of product. Units should be tested regularly.