



## 8200

### Specifications

**Shower Head:** 10" ABS plastic in Safety Green (8129FC)

**Activation:** Rigid stainless steel pull rod operates a stay open chrome plated brass ball valve that is equipped with a stainless steel stem.

**Standard:** 9" diameter floor flange with 1-1/4" galvanized steel pipe. Stanchion incorporates an exclusive cast air gap/supply fitting that separates supply and waste. Two 21" long self adhesive high visibility stripes in Safety Green and bright yellow to improve visibility.

### EYE/FACE WASH

**Receptor:** Safety green ABS plastic with UV inhibitors resistant to damage from alkalies, salt solutions, oils, most acids, sun exposure, color change and brittleness.

**Heads:** Patented Omni-flo, wrap around spray head provides superior spray pattern that gently covers entire facial area. Includes permanent, one-piece, hinged dust cover of bright yellow durable ABS plastic. Positive link actuation assures instant opening, while providing positive cover retention.

**Dust cover:** Durable ABS bright yellow dust cover completely covers the eyewash spray head and protect unit from dust and other environmental contamination. Positive link actuation assures instant opening, while providing positive cover retention.

### Disclaimer:

Illustrations, detail drawings and accompanying descriptions describe standard features and sometimes optional variations of each product. They do not necessarily show or describe all the variations available. All designs are subject to change without notice and unless stated in the order, material will be furnished of design in effect at the time the order is filled. As may be necessary, we reserve the right to substitute materials and/or to make changes in design or other specification, as shown and described in any of our printed literature, without liability to purchasers.

Notice: Model shown meet **ANSI** standard and **OSHA** rules and regulations relating to this type of product. Units should be tested regularly.

**Activation:** Rigid stainless steel push flag and ABS foot treadle operate a stay open type stainless steel ball valve that is equipped with a stainless steel ball and stem.

**Sign:** Universal emergency sign included.

**Stream Control:** Steady water flow under varying pressures assured with automatic pressure compensation devices.

**Strainer:** Fully serviceable in-line, 50x50 mesh strainer filters debris from reaching the eyewash.

### DETAILS

**Supply:** 1-1/4" IPS

**Waste:** 1-1/4" IPS



*\* picture shown after installation and for illustration purpose only*