



**1455 Kleppe Lane, Sparks, NV 89431-6467 * (775) 359-4712 * fax: (775) 3597424
** Bachweg 3, CH-3401 Burgdorf, Switzerland *(34) 423 2300 * fax: (34) 423 2301
** 5 Woodlands Terrace #03-01 Singapore 738430 * (65) 6367 0359 * fax: (65) 6269 4110
* e-mail: hawsmfg@singnet.com.sg website: www.hawasco.com

8317CTFP. 230V

A fully assembled, ready to install, cable traced freeze resistant unit with top supply.

Specifications

Shower Head: 10" ABS plastic in Safety Green with 20GPM flow control.

Activation: Rigid stainless steel pull rod operates a stay open ball valve that is equipped with a stainless steel stem.

Standard: 9" diameter floor flange with 1-1/4" stainless steel piping.

Jacket: Safety Green, UV resistant, ABS plastic with removable polyethylene foam insulation. Includes elastomeric seal for added weather protection.

Voltage: 230V, 50 Hz, single phase.

Eye/Face Wash

Heads: Twin Feather-Flo patented ABS plastic eye/face wash heads in Safety Green with integral flip top dust covers that protect heads and automatically release with water pressure.

Activation: Stainless steel push flag operates a stay open ball valve that is equipped with a stainless steel ball and stem.

Electric cable: Reliable self-regulating heat cable with external braid, guards against overheating and cold spots.

Thermostat: The temperature control thermostat shuts off heat at 15C-25C.

Freeze Protection Bleed valve: Flushes water through line when internal water temperature drops below 2C. Closes at 7C.

Disclaimer:

Illustrations, detail drawings and accompanying descriptions describe standard features and sometimes optional variations of each product. They do not necessarily show or describe all the variations available. All designs are subject to change without notice and unless stated in the order, material will be furnished of design in effect at the time the order is filled. As may be necessary, we reserve the right to substitute materials and/or to make changes in design or other specification, as shown and described in any of our printed literature, without liability to purchasers.

Junction Box: Stainless steel junction box

Certifications: ATEX & NEPSI Cert

Ex Protection type: II 2GD ExD IIC Ex tD A21 IP66

DETAILS

Supply: 1-1/4" NPT (F)



** picture shown after installation and for illustration purpose only*

Notice: Model shown meet ANSI standard and OSHA rules and regulations relating to this type of product. Units should be tested regularly.