



model **7778B**
Axion MSR™ Eye/Face Wash

FEATURES & BENEFITS

STRAINERS/FILTERS

Type 304 Stainless Steel in-line 50 x 50 mesh water strainer supplies added protection against corrosion and prevents debris from reaching the eye/face wash so the 8330 stays functioning at its best. Strainer is easily serviceable. Stainless steel dust cover protects eye/face wash head as well as bowl up until the last second before use further optimizing operation.

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit

VALVES

Type 316 Stainless Steel ball valve is designed to make the flushing of fluid occur with the simple push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide a superior protection against corrosion and breakage.

QUALITY CONTROL

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with pre-assembled 16 gauge Type 304 Stainless Steel wall bracket to assist with the installation process.

EYE/FACE WASH

AXION MSR™ eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.



SPECIFICATIONS

Model 7778B wall-mounted eye/face wash shall include a stainless steel 11" round bowl, an AXION MSR™ eye/face wash head with inverted directional laminar flow which achieves zero vertical velocity supplied by an integral flow control, and stainless steel ball valve equipped with stainless steel ball and stem. Unit shall also include stainless steel wall bracket, stainless steel dust cover, universal sign, 1/2" IPS inlet, and 1-1/4" IPS waste.

OPTIONS

- Tempered Water Blending Valves: Model 9201EFE; emergency valve thermostatically mixes hot and cold water to provide a safe fluid supply for emergency eyewash equipment, with a flow rate of 12 gpm.
- Tempered Water Blending Systems: Model TWBS.EWE; low-lead emergency valve thermostatically mixes hot and cold water to provide a safe fluid supply for emergency eyewash equipment, with a flow rate of 12 gpm.

To see all options for this model, visit www.hawsc.com

APPLICATIONS

In an environment where materials need to withstand the greatest corrosion, where eyes and face of any person may be exposed to these injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes and face shall be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7778B is certified by CSA to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.

