

FEATURES & BENEFITS

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit

EYE/FACE WASH VALVE

Valve is designed so full continuous flow occurs with the simple squeeze of a lever providing an easy start to the irrigation process.

HOSE

The 12' recoil swivel hose delivers an extended coverage area and is pressure rated at 200 psi to optimize durability.

MOUNTING

Wall-mounted design with wall hook allows for easy locating as well as a space efficient piece of emergency equipment.

EYE/FACE WASH

AXION MSR™ eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

OPTIONS

- Vacuum Breaker: Model SP212 is a chrome-plated brass vacuum breaker.
- Repair Kit: Model VRKSP248 valve repair kit for Model SP248 squeeze handle valve.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.
- Tempered Water Blending Valves: Model 9201EFE; emergency valve thermostatically mixes hot and cold water to provide a safe fluid supply for emergency eyewash equipment, with a flow rate of 12 gpm.

To see all options for this model, visit www.hawsco.com



SPECIFICATIONS

Model 8905 wall mounted eye/face wash and body spray shall include an AXION MSR™ eye/face wash head which features an inverted directional laminar flow which achieves zero vertical velocity supplied by an integral flow control, chrome plated brass stay-open squeeze lever valve, 12-foot yellow recoil hose with chrome-plated swivel fitting at one end, universal sign, and 1/2" IPS inlet. In order to comply with state codes the use of a vacuum breaker is required with all hand held eye/face wash body spray units (Haws offers model SP212)

APPLICATIONS

Perfect for the environment where safety is of the utmost importance and an extended coverage area may be needed. When installed properly, the functional constructed, wall mounted design of the 8905 is not only space efficient it meets the current ANSI standards of the Federal State Drinking Water Act.

Unit 8905 is certified by CSA to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.