



**1455 Kleppe Lane, Sparks, NV 89431-6467 * (775) 359-4712 * fax: (775) 3597424
** Bachweg 3, CH-3401 Burgdorf, Switzerland *(34) 423 2300 * fax: (34) 423 2301
** 5 Woodlands Terrace #03-01 Singapore 738430 * (65) 6367 0359 * fax: (65) 6269 4110
* e-mail: hawsmfg@singnet.com.sg website: www.hawscos.com

8560

Specifications

Designed for high hazard areas. Thorough drenching of entire body within seconds.

Shower

Nozzles: 18 chrome plated brass, full-cone, direction pre-set, non-adjustable, plus four weep sprays for drainage.

Activation: Stainless steel push flag operates a stay open stainless steel ball valve that is equipped with a stainless steel stem. Valve can be activated when approached from either direction.

Panels: Safety green ABS plastic with a universal emergency sign.

Standard: Hot dip galvanized steel pipe.

DETAILS

Supply: 1" NPT (F)



** picture shown after installation and for illustration purpose only*

Disclaimer:

Illustrations, detail drawings and accompanying descriptions describe standard features and sometimes optional variations of each product. They do not necessarily show or describe all the variations available. All designs are subject to change without notice and unless stated in the order, material will be furnished of design in effect at the time the order is filled. As may be necessary, we reserve the right to substitute materials and/or to make changes in design or other specification, as shown and described in any of our printed literature, without liability to purchasers.

Notice: Model shown meet ANSI standard and OSHA rules and regulations relating to this type of product. Units should be tested regularly.