



# model 8605WC

Barrier-Free Emergency Equipment

## FEATURES & BENEFITS

### CONSTRUCTION

Reinforced molded fiberglass booth provides a solid free standing enclosed environment for added privacy and stability. Unit also comes equipped with galvanized steel floor grate for wheel chair access while offering proper waste drainage.

### VALVES

Eye/face wash and shower ball valves are designed to make the flushing of fluid remains occur with the simple pull of a lever or push of a stainless steel flag.

### BARRIER-FREE ACCESS

Barrier-free design offers a low profile eyewash assembly and a longer shower pull rod allowing for wheel chair access.

### QUALITY CONTROL

Entire unit is pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and an added peace of mind.

### EYE/FACE WASH

AXION MSR™ eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

### SHOWER HEAD

AXION MSR™ ABS plastic drench showerhead uses a hydrodynamic design to give equal distribution of water throughout the entire footprint of flow.



## SPECIFICATIONS

Model 8605WC barrier-free combination shower and eye/face wash booth shall include an AXION MSR™ eye/face wash head shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral flow control. Unit shall also include the AXION MSR™ hydrodynamic designed ABS plastic shower head with flow control, wheel chair accessibility, chrome-plated brass stay-open shower and eyewash ball valves equipped with stainless steel ball and stem, a white reinforced molded fiberglass booth, galvanized steel floor grate, universal signs, 1" IPS supply, and 3" caulk floor drain.

## OPTIONS

- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by an 1-1/4" double pole, double throw flow switch.
- Shower Test Kit: Model 9010 shower test kit.
- Privacy Curtain: Model 9040, privacy curtain designed to be used with 3-sided free standing combination emergency drench shower and eye/face wash units.

To see all options for this model, visit [www.hawsc.com](http://www.hawsc.com)

## APPLICATIONS

Where the eyes, face, or body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes, face, and body shall be provided within the work area for immediate emergency use. Emergency eye/face wash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8605WC is certified by CSA to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.

