

Model 7655WC barrier-free recessed wall-mounted eye/face wash features a single-action pull down to activate twin Feather-Flo® eye/face wash mounted in a fully recessed stainless steel cabinet. Supply: 1/2" IPS.

Model 7655WC is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

Components:

Eye/Face Wash Head: Model SP21FC Feather-Flo® ABS green plastic eye/face wash head with built-in 2.5 gpm flow control with integral flip top dust cover that automatically releases with flow of water. 1/4" IPS.

Cabinet: Part Number 0001438155 fully recessed Type 304 stainless steel with No. 4 satin finish. Size: 15" W x 27" H, 4" D.

Universal Sign: Model SP175 vertical universal emergency eyewash sign. Size: 8" x 10-3/4".

Test This Week Tag: SP170 is a green waterproof test card with space for date and initials of inspector. Used to record weekly testing of emergency equipment.

7655WC



Options/Accessories: (Additional costs may apply)

Barrier-Free Eye/Face Wash: Model 7656WC barrier-free recessed wall-mounted pull down eye/face wash with stainless steel drain pan.

Tempered Water Blending Systems: Model TWBS.EW, tempered water blending system, prepackaged, fully engineered and tested system with redundant fail-safe features to produce up to 5 gpm tempered water for eyewashes.

Tempered Water Blending Valves: Model 9201 thermostatic mixing valve that mixes hot and cold water for the tempering of water for eyewash units. Maximum flow rate is 21 gpm.

Discontinued Emergency Equipment: Model 8355WC barrier-free combination wall-mounted full recessed eye/face wash and flush to ceiling-mounted shower. Eyewash with drain pan and pull down lever valve for shower are incorporated in stainless steel wall cabinet.

DISCLAIMER: Continued product improvements make specifications subject to change without notice. Check www.hawsco.com for the latest product information and updates.