



HAWS MANUFACTURING PTE LTD

** 2A Sungai Kadut Drive, Singapore 729554 * (65) 6367 0359 * fax: (65) 6269 4110
* e-mail: enquiry@haws.sg website: www.haws.sg

8317CTFPT cw bowl

A fully assembled, ready to install, cable traced freeze resistant unit with top supply.

Specifications

Shower:

Head: 10" stainless steel shower head with 20GPM flow control.

Activation: Rigid stainless steel pull rod operates a stay open S316 ball valve that is equipped with a stainless steel stem.

Standard: 9" diameter floor flange with 1" and 1-1/4" galvanized piping.

Jacket: Safety Green, UV resistant, ABS plastic with removable polyethylene foam insulation.

Junction box: Malleable iron bodies, suitable for Class 1, Div 2 area. Meet IP56.

Eye/Face Wash

Receptor: 11" stainless steel S304 with #7 bright finish on exterior.

Heads: Twin Feather-Flo patented ABS plastic eye/face wash heads in Safety Green with integral flip top dust covers that protect heads and automatically release with water pressure.

Activation: Stainless steel push flag and foot treadle operate a stay open S316 ball valve that is equipped with a stainless steel ball and stem.

Electric cable: Reliable self-regulating heat cable with external braid, guards against overheating and cold spots.

Thermostat: Temperature control thermostat shuts off heat at 25 deg C to 15 deg C.

Freeze Protection Bleed valve: Flushes water through line when internal water temperature drops below 2C. Closes at 7C.

Disclaimer:

Illustrations, detail drawings and accompanying descriptions describe standard features and sometimes optional variations of each product. They do not necessarily show or describe all the variations available. All designs are subject to change without notice and unless stated in the order, material will be furnished of design in effect at the time the order is filled. As may be necessary, we reserve the right to substitute materials and/or to make changes in design or other specification, as shown and described in any of our printed literature, without liability to purchasers.

Voltage: 230V, 50 Hz, single phase, AC

Supply: 1" NPT (F)

Waste: 1" NPT (F)

****Freeze protection of water supply connection to unit by others.**



Notice: Model shown meet ANSI standard and OSHA rules and regulations relating to this type of product. Units should be tested regularly.