



## 8600

### Specifications

#### Shower unit

**Booth:** Reinforced molded fiberglass, enclosed on three sides, alkali and acid resistant, bright white finish. Molded anchoring pads provided.

**Shower Nozzles:** 7 stainless steel, direction pre-set, full cone nozzles located over head and on the sides of the shower booth.

**Activation:** Weight on treadle opens chrome plated brass self closing globe valve which activates all shower nozzles.

**Activation:** Weight on 30" x 30" open type galvanized subway treadle grate opens chrome plated brass self closing globe valve.

**Sign:** Large universal emergency sign included.



#### Eye/face Wash

**Heads:** Twin Feather-Flo patented ABS plastic eye/face wash heads in Safety green with integral flip top dust covers that protect heads and automatically release with water pressure.

#### Stream Control:

Steady water flow under varying pressures assured with dual automatic pressure compensation devices.

#### DETAILS

**Shower Supply:** 1" NPT (F)

**Shower drain:** 3" inside caulk

#### Options (additional cost):

**Model 9040:** Privacy curtain

**Model 9001:** Alarm system

#### Disclaimer:

*Illustrations, detail drawings and accompanying descriptions describe standard features and sometimes optional variations of each product. They do not necessarily show or describe all the variations available. All designs are subject to change without notice and unless stated in the order, material will be furnished of design in effect at the time the order is filled. As may be necessary, we reserve the right to substitute materials and/or to make changes in design or other specification, as shown and described in any of our printed literature, without liability to purchasers.*

Notice: Model shown meet ANSI standard and OSHA rules and regulations relating to this type of product. Units should be tested regularly.