

FEATURES & BENEFITS

BOOTH CONSTRUCTION

Foam-insulated, membrane encapsulated wooden structure makes the entire composition of booth carry a total R-value of 11. Bright yellow elastomeric membrane is waterproof, chemically resistant, and protected with UV inhibitors for a long lasting finish.

FLOW CONTROLS

Green ABS designed plastic showerhead and Feather-Flo eyewash heads equipped with integral self-regulating 20 gpm shower control and 2.5 gpm (2) eyewash control allow both parts of the emergency equipment to be safely used simultaneously.

QUALITY CONTROL

Fully assembled and Engineer tested product that is ready for placement and hook-up.

ALARM SYSTEM

Standard with audible and visible alarms controlled by a flow switch for immediate attention to an emergency.

SPACE HEATER

Wall mounted natural convection 2.5 kw space heater provides moderate booth temperatures under any cold weather climate conditions.

ELECTRICAL SYSTEM OPTIONS

Option 31: Nema 4 water/dust tight. Option 32: Class I, Division 2, Groups B, C and D. Option 33: Class I, Division I, Groups C and D

OPTIONS

- ❑ Enclosed Emergency Environments: There are a variety of possibilities for your application. Please write to engineeredolutions@hawasco.com to discuss.

To see all options for this model, visit www.hawasco.com



SPECIFICATIONS

Model 8730 heated enclosed shower and eye/face wash shall include an all-weather foam-insulated 4' x 4' booth made of a membrane encapsulated wooden structure with bright yellow elastomeric chemically resistant waterproof coating, protected with UV inhibitors, and has an R-value of 11. The booth shall also include dual spring-loaded, self-closing shower doors, and is trimmed with large directional arrows, universal shower/eyewash sign, fiberglass floor grate, and 3" inside caulk drain. The shower and eye/face wash shall include a green ABS plastic 10-5/8" showerhead with integral self-regulating 20 gpm flow control, twin Feather-Flo® ABS plastic eye/face wash heads integral flip top dust covers, chrome-plated brass stay-open shower, eyewash, and drench hose ball valves equipped with stainless steel ball and stem, and protected by scald and freeze bleed valves. The internal booth temperature is maintained by a natural convection 2.5kw space heater. The standard alarm system is flow switch activated, and provides local audible and visible alarms. The electrical system requires 208/240 VAC single phase, 3 wire 15 amp minimum (other voltages available upon request). Combination shower and eyewash is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

APPLICATIONS

Perfect for Petro-chemical, bio-diesel, and ethanol processing facilities, and other remote outdoor locations where drench showers with very cold water would pose a health hazard to employees and a liability to employers, or in shower areas exposed to cold air and wind where showering with very cold water could discourage proper flushing time.